



WING WALK COMPOUND

Wing Walk Compound comes in two colors, black or gray. Wing Walk is a brush-on coating for wing walks or any areas where a gritty, non-skid walkway is desired. It is formulated to remain relatively soft throughout its service life to promote adhesion and prevent chipping. Use directly out of the can. If the compound is too thick for the intended use, it may be thinned 5 to 1 with toluene. **COVERAGE:** One unthinned gallon covers approximately 150 square feet with one coat.

X1567B-QT Black U.S. Quart
X1567B-GAL Black U.S. Gallon
X1567G-QT Gray U.S. Quart



RANDOLPH FAST DRY ENGINE ENAMELS

Engine Enamels are formulated to use on engine crankcases and cylinders usually after engine overhaul or for general maintenance. They are heat resistant and provide good gloss and color retention. Engine Enamels thinned 5 to 1 with 257 Enamel Thinner. **COVERAGE:** One thinned gallon covers approximately 225 square feet with one coat.

303-QT BLACK
D5973-QT CONTINENTAL GOLD
G5436-QT LYCOMING GRAY



FLATTENER

Flattener is a liquid product with silica flattener added. It is used to reduce the gloss of Butyrate Dope, Enamel, or Ranthane. Adding flattener in increasing amounts can result in semi-gloss or full military flat depending on the percentage added. Flattening is an inexact science; it is always best to spray a sample then let it dry to insure you are achieving the flatness desired.

FT- PT



FLOAT LACQUER

Float lacquer is a time-honored silver coating for aircraft floats. Although it can be applied by brush, it is more suitable for spraying. Float lacquer is a classic, low-tech way of coating floats. Although its service life is far less than today's polyurethanes, its ease of application and repair make it a useful product. Apply over epoxy-primed metal or directly over old float lacquer. Float lacquer is thinned 1 to 1 with 286 Nitrate Thinner. **COVERAGE:** 225 square feet per gallon.

FL-GAL



RANDOLPH ACID-PROOF PAINT

This specialty product from Randolph Products is used as a spray on the bottom of aluminum floats on amphibious aircraft to protect them from marine growth. It is also an excellent product for use in battery compartments. Manufactured to Military Spec. TT-L-54.

345-QT
345-GAL



257 ENAMEL THINNER

Enamel thinner is a special formulation for enamel only. Mix 1 to 5 with enamel for spray viscosity.

257-QT
257-GAL



C-2210 PAINT SURFACE CLEANER

A mild solvent cleaner used to clean surfaces before spray painting.

C2210-QT
C2210-GAL



286 NITRATE THINNER

286 Thinner is used to reduce G-6302 Rand-O-Proof, W-7868 Non-Tautening Nitrate Dope (Blue) and E-4964 Non-Tautening Nitrate (Clear). 286 Thinner is mixed 1 to 1 with nitrate dopes for brushing or spray viscosity.

286-QT
286-GAL
286-5GAL

GOULET FLOAT SEALER

Elastic fluid consistency product formulated to seal pin holes around rivets and seams in floats.

DIRECTIONS - Pour a suitable quantity in each float compartment and slop liquid around compartment interior allowing sealer adequate time to flow into seams and voids. Rotate float if necessary.

FS2005-GAL