



LIGHT WEIGHT, SELF-LOCKING, 450° F NUTS

Steel, heat treated, cadmium plated, dry film lubricated. For use in applications up to 450° F. Meets salt spray requirements.

Particularly suited for use in blind close clearance areas. The counterbore provided eliminates necessity for shimming to prevent bottoming on the imperfect thread.

For countersunk rivet holes add K to NAS Part Number or BC to Mfr's Part Number. For example: NAS680A-06K or RM52LHTA51-62BC. Prices on application. Larger sizes also POA.

Order from this page by NAS Number.

	NAS NUMBER	MS NUMBER	MANUFACTURER'S PART NUMBER	THREAD SIZE	WRENCH SIZE	PKG. QTY.	
	NAS679A	NAS679A-06W	MS21040-L06	RMLHTM-62W	6-32	5/16"	100
		NAS679A-08W	MS21040-L08	RMLHTM-82W	8-32	11/32"	100
		NAS679A-3W	MS21040-L3	RMLHTM-02W	10-32	3/8"	100
		NAS679A-4W	MS21040-L4	RMLHTE-048W	1/4-28	7/16"	50
		NAS679A-5W	MS21040-L5	RMLHTE-054W	5/16-24	1/2"	50
		NAS679A-6W	MS21040-L6	RMLHTE-064	3/8-24	9/16"	50
	NAS1291	NAS1291-06	MS21042-L06	RM52LH3324-62	6-32	3/16"	100
		NAS1291-08	MS21042-L08	RM52LH3324-82	8-32	7/32"	100
		NAS1291-3	MS21042-L3	RM52LH3324-02	10-32	1/4"	100
		NAS1291-4	MS21042-L4	RM52LH3324-048	1/4-28	5/16"	100
		NAS1291-5	MS21042-L5	RM52LH3324-054	5/16-24	3/8"	50
		NAS1291-6	MS21042-L6	RM52LH3324-064	3/8-24	7/16"	50

	NAS NUMBER	MANUFACTURER'S PART NUMBER	THREAD SIZE	RIVET HOLE SPACING	RIVET HOLE SIZE	PACKAGE QTY.	
	NAS680A	NAS680A-06	RM52LHTA51-62	6-32	.68	.098	50
		NAS680A-08	RM52LHTA51A-82	8-32	.68	.098	50
		NAS680A-3	RM52LHTA51A-02	10-32	.68	.098	50
		NAS680A-4	RM52LHTA51-048	1/4-28	1.00	.098	25
		NAS680A-5	RM52LHTA51-054	5/16-24	1.00	.130	25
		NAS680A-6	RM52LHTA51-064	3/8-24	1.00	.130	25
	NAS682A	NAS682A-06	RM52LHTA57-62	6-32	.312	.098	50
		NAS682A-08	RM52LHTA57-82	8-32	.312	.098	50
		NAS682A-3	RM52LHTA57-02	10-32	.312	.098	50
		NAS682A-4	RM52LHTA57-048	1/4-28	.312	.098	25
		NAS682A-5	RM52LHTA57-054	5/16-24	.312	.130	25
	NAS686A	NAS686A-06	RM52LHTA521-62	6-32	.68	.098	50
		NAS686A-08	RM52LHTA521-82	8-32	.68	.098	50
		NAS686A-3	RM52LHTA521-02	10-32	.68	.098	50
		NAS686A-4	RM52LHTA521-048	1/4-28	1.00	.098	25
		NAS686A-5	RM52LHTA521-054	5/16-24	1.00	.130	25
		NAS686A-6	RM52LHTA521-064	3/8-24	1.00	.130	25
	NAS697A	NAS697A-06	RM52LHTA51M-62	6-32	.343	.066	50
		NAS697A-08	RM52LHTA51M-82	8-32	.468	.098	50
		NAS697A-3	RM52LHTA51M-02	10-32	.500	.098	50
		NAS697A-4	RM52LHTA51M-048	1/4-28	.562	.098	25
		NAS697A-5	RM52LHTA51M-054	5/16-24	.718	.130	25
	NAS698A	NAS698A-06	RM52LHTA55M-62	6-32	.243	.066	50
		NAS698A-08	RM52LHTA55M-82	8-32	.331	.098	50
		NAS698A-3	RM52LHTA55M-02	10-32	.354	.098	50
		NAS698A-4	RM52LHTA55M-048	1/4-28	.398	.098	25
		NAS698A-5	RM52LHTA55M-054	5/16-24	.508	.130	25
	NAS1068A	NAS1068A-06	RM52LHTA521M-62	6-32	.343	.066	50
		NAS1068A-08	RM52LHTA521M-82	8-32	.468	.098	50
		NAS1068A-3	RM52LHTA521M-02	10-32	.500	.098	50
		NAS1068A-4	RM52LHTA521M-048	1/4-28	.562	.098	25