

Goulet Aircraft Supply Ltd.



Head Office

59 Eagle Drive
Winnipeg, MB R2R 1V4
Telephone: (204) 783-8512
Fax: 1-888-783-3302
E-mail: sales@gouletaircraft.com

Branch Office

48 Airport Road
Edmonton, AB T5G 0W7
Telephone: (780) 452-4242
Fax: 1-888-454-4050
E-mail: goulaced@telus.net

Website: <http://www.gouletaircraft.com>

Taylor

Pneumatic Tool Company

T-7788K

3/8" Reversible Drill
w/ Keyless Chuck (T-#2, T-#3 not shown)



RPM 2500
Weight 2 lbs.
Length 7-1/4"
Air Inlet 1/4" NPT
Air Pressure 90 PSI Max.

*Rear Exhaust

*Quality hardened gears

*Convenient forward and reverse lever

*Lightweight aluminum handle

T-4X

Pistol Grip
.401 Rivet
Hammer

(T-2X, T-3X not shown)



Model #	T-2X	T-3X	T-4X
Shank Diameter	.401	.401	.401
Bore & Stroke	1/2"x2-1/4"	1/2"x2-7/8"	1/2"x3-1/16"
Blows per Min.	2600	2100	1700
Length	6-11/16"	7-5/16"	8-5/16"
Weight	2-1/4 lbs.	2-5/16 lbs.	2-3/4 lbs.
Air Pressure	90 PSI Max.	90 PSI Max.	90 PSI Max.

*Extra sensitive teasing throttle

*Lightweight aluminum handle

*Hardened tool steel piston and steel alloy cylinder for long life

*Spool valve for slow heavy blows needed to drive rivets

T-7888 1/4" Palm Drill



RPM 2800
Drill Chuck Size 1/4"
Weight 1.25 lbs.
Air Inlet 1/4" NPT
Air Pressure 90 PSI Max.

The T-7888 is a small precision 1/4" drill with plenty of power that fits in the palm of your hand.

T-7888-1B 1/4" Palm Drill w/ 1B Chuck

Same great tool as the T-7888, but with a more precise Jacob 1B chuck.

T-7759R 1/4" Angle Die Grinder

Also available is the T-7759 front exhaust. Angle Die Grinder



RPM	25,000	*Hardened spiral bevel gears
Collet Size	1/4"	
Length	6-5/8"	
Weight	1 lbs.	*Grease fitting in head
Air Pressure	90 PSI Max.	
Air Inlet	1/4" NPT	*.25 HP

Angle design provides comfortable grip. Strong and reliable, the T-7759R is excellent for grinding, polishing, deburring and breaking sharp edges in confined areas. 1/8" collet available (T-7508).

*Full ball bearing construction
*Lockoff lever

T-9750 90 Degree Angle Drill



RPM	2800	*Compact
HP	.33	
Spindle	1/4"-28 female thread	*Lightweight
Weight	1.6 lbs.	
Length	10"	*Variable speed throttle
Air Inlet	1/4" NPT	
Air Pressure	90 PSI Max.	*Uses 1/4"-28 threaded drill bits

Primarily used in the aircraft manufacturing and repair industry, the T-9750 is designed to insure precision holes for critical applications. The angle head may be rotated 360 degrees to allow ideal orientation to the throttle. Ribbed handle for secure grip. Mini grease fitting in angle head. Rear exhaust. Head height = 1.025" width = .670

T-9751

45 Degree Angle Drill



RPM	2800	*Compact
HP	.33	
Spindle	1/4"-28 female thread	*Lightweight
Weight	1.6 lbs.	
Length	10"	*Variable speed throttle
Air Inlet	1/4" NPT	
Air Pressure	90 PSI Max.	

Same great motor and gears as the T-9750, but with a 45 degree angle head. Uses 1/4"-28 threaded drill bits.

T-7015

Jam Gun & Cup



Cup Capacity 8 fl. oz.
Air Pressure 40 to 90 PSI Max
Air Consumption 2 to 4 CFM
Nozzle Tip 1.8mm

*Ideal for touch up, shading and spotting

*Pin point accuracy

T-7891 3/16" Heavy Duty Riveter

Capacity 3/16"
Pulling Force 2300 lbs.
Stroke adjustable to 9/16"
Height 10-1/4"
Weight 3-1/8 lbs.
Air Inlet 1/4" NPT
Air Pressure 90 PSI Max.



*Heavy duty construction

*Hardened jaw and nosepiece

*Ideal for steel, stainless steel, aluminum, formica and masonite

* Tool includes 3/16", 5/32", 1/8" and 3/32" nosepieces.

T-7007

Spray Gun & No Drip Cup




Cup Capacity One Quart
Nozzle Tip 1.8mm
Fluid Inlet 3/8" NPS
Weight Gun & Cup 1.2 lbs.
Air Pressure 30 to 70 PSI
Air Consumption 8.5 to 12 CFM
Compressor Required 1-1/2 HP Min.

Designed for spraying all refinishing materials, including varnishes, urethanes, primers, lacquers, enamels and acrylics. Sprays a wet heavy pattern.

T-7311

6" DA Sander



RPM	10,000	*Built-in regulator
Pad Diameter	6"	
Length	19-19/64"	*1/2 HP motor
Weight	1.7 lbs.	
Air Pressure	90 PSI Max.	*Full ball bearing construction
Air Inlet	1/4" NPT	
Hose Size	3/8" ID	*Built-in silencer

The T-7311 is built for fast material removal, blending body filler, contouring patches and sanding pre-paint preparation.

*Balanced counter weight design is smooth for longevity

T-7711

Nibbler



Strokes per min.	2,600	*Teasing Throttle
Width of cut	7/32"	
Max. Steel Thickness	18 gauge	*1/2 HP motor provides power through hardened planetary gear system
Length	7"	
Weight	2.2 lbs.	
Air Inlet	1/4" NPT	*Cutting head adjustable 360 degrees in 90 degree increments
Air Pressure	90 PSI Max	

The T-7711 cuts sheet metal leaving a clean distortion free cut. This tool is a must for every body shop and sheet metal shop. Easily cuts circles and contoured shapes.

T-7728

3/8" Ratchet Wrench



RPM	375	
Bolt Capacity	3/8"	*Teasing throttle
Square Drive	3/8"	
Max. Torque	50 ft. lbs.	*Ball type socket retainer
Max. Torque by Hand	125 ft. lbs.	
Length	10"	*Convenient forward and reverse button
Weight	2-1/2 lbs.	
Air Inlet	1/4" NPT	*Light, easy to grip aluminum handle
Air Pressure	90 PSI Max.	

The T-7728 is one of the most useful tools around. Great for hard to reach fasteners.

T-7788 3/8" Drill

RPM	2,500
Drill Chuck Size	3/8"
HP	.5
Length	7"
Weight	2 lbs.
Air Inlet	1/4" NPT
Air Pressure	90 PSI Max.



- *Quality hardened gears
- *Rear Exhaust
- *Variable Speed
- *Lightweight aluminum handle

The T-7788 is great for those tough jobs that need extra power. Excellent tool for honing, reaming, wirebrushing, hole sawing and heavy duty drilling.

T-7402

1/8" Pencil Grinders



Model #	T-7402	
RPM	70,000	*Precision ball bearings
Collet	1/8"	
Length	5-1/2"	*Rear Exhaust
Weight	3-3/4 oz.	

The perfect tools for cleaning and polishing dies, porting and polishing engines, de-burring castings, and any job where carbide burrs are used for delicate material removal.

- *1/8" collets
- *Twist throttle

T-7720 3/8" Butterfly Impact

Bolt Capacity	3/8"
Square Drive	3/8"
Max. Torque	125 ft. lbs.
Length	6-1/4"
Weight	2 lbs.
Air Inlet	1/4" NPT
Air Pressure	90 PSI Max.



- *Paddle style forward and reverse lever
- *Built-in regulator
- *Ring type socket retainer
- *Protective rubber scuff guard

Our T-7720 features a 360 degree swivel regulator. Its lightweight and compact size lets you reach the tightest fasteners.

T-7757R

1/4" High Speed Die Grinder



Free Speed RPM	25,000	*Direct drive
Collet Size	1/4"	
Length	6-5/8"	*Rear Exhaust
Weight	1-3/8 lbs.	*Full ball bearing construction
Air Pressure	90 PSI Max.	*Powerful .5HP motor
		*Lockoff lever

Compact to work in close quarters, the T-7757R cannot be damaged by overloading. Drill, brush, hone, deburr without hazard of electric shock. (Not for use with cast wheels or accessories not rated for 25,000 RPM.) Optional 1/8" collet available (T-7508).

T-7788R 3/8" Reversible Drill

RPM	2,500
Drill Chuck Size	3/8"
HP	.5
Length	7"
Weight	2 lbs.
Air Inlet	1/4" NPT
Air Pressure	90 PSI Max.



- *Quality hardened gears
- *Rear Exhaust
- *Variable Speed
- *Lightweight aluminum handle

The T-7788R is great for those tough jobs that need extra power. Excellent tool for honing, reaming, wirebrushing, hole sawing and heavy duty drilling.

T-7700

Heavy Duty Metal Shear



Steel Capacity	18 gauge
RPM	2200
Length	8-1/4"
Weight	3 lbs.
Air Inlet	1/4" NPT
Air Pressure	90 PSI Max.

Make distortion free cuts with the T-7700 and T-7701. The blades shear the material giving a clean cut. A 1/4" strip of material is removed by the cutting action or can be used to trim one edge. Loosen one screw and head rotates 360 degrees.

- *Cuts up to 18 gauge sheet metal
- *Lightweight, easy to maneuver
- *3 gear planetary gear system
- *Head rotates 360 degrees

T-7724

3/8" Pistol Grip Impact

Bolt Capacity	3/8"
Square Drive	3/8"
Max. Torque	100 ft. lbs.
Length	6-1/4"
Weight	2 lbs.
Air Inlet	1/4" NPT
Air Pressure	90 PSI Max.



- *Light easy to grip aluminum handle
- *Built-in regulator
- *Ring type socket retainer
- *Protective rubber scuff guard

The T-7724 has a convenient forward and reverse switch. The rocking dog clutch is designed for maximum durability.

T-7758R

1/4" Rear Exhaust Die Grinder



RPM	25,000	*Direct drive
Collet Size	1/4"	
Length	5-1/2"	*Rear Exhaust
Weight	13/16 lbs.	
Air Pressure	90 PSI Max.	*Full ball bearing construction
Air Inlet	1/4" NPT	

The T-7758R fits in the palm of your hand. Easy accessibility to confined areas.

- *Powerful .25HP motor
- *Lockoff lever

1/8" collet available (T-7508).

T-7801

3" Cutoff Tool



RPM	22,000	*Precision ball bearings
Wheel Size	3"	
Arbor Size	3/8"	*Rear Exhaust
Length	7-3/4"	
Weight	1-3/4 lbs.	*Fast smooth 1/2 HP motor
Air Pressure	90 PSI Max.	
Air Inlet	1/4" NPT	*Built-in regulator

When plenty of reliable power is needed, the T-7801 will provide it. Cuts sheet metal, fiberglass, muffler clamps and hangers. Grinds burrs and rough edges.

- *Lockoff lever

