


# WASHERS

## AN960 FLAT WASHERS



**AN960-4** is a regular size washer for a #4 screw in **Cadmium Plated Steel**

**AN960-C4** is the same, but in **Stainless Steel**.

**AN960-D4** is unplated **Aluminum Alloy**.

To order any of these in **Light Series** (see thickness column), add the letter "L" at the end of the dash number:

**AN960-4L**

Sold only in packages of 100.

AN DASH NUMBER	Screw or Bolt Size	I.D.	O.D.	THICKNESS	
				REGULAR Series	LIGHT Series
-4	#4	.125	.312	.032	.016
-6	#6	.149	.375	.032	.016
-8	#8	.174	.375	.032	.016
-10	#10	.203	.438	.064	.032
-416	1/4	.265	.500	.064	.032
-516	5/16	.326	.562	.064	.032
-616	3/8	.390	.625	.064	.032
-716	7/16	.453	.750	.064	.032
-816	1/2	.515	.875	.064	.032
-916	9/16	.578	1.062	.064	.032
-1016	5/8	.640	1.188	.091	.032

## AN970 LARGE AREA FLAT WASHERS

Steel, Cadmium Plated per Spec. QQ-P-416. Practical for use on wood because of large bearing area. Sold only in packages of 100.



AN970 DASH NUMBER	SCREW OR BOLT SIZE	INSIDE DIA. (Inches)	OUTSIDE DIA. (Inches)	THICKNESS (Inches)
-3	#10	.1935	7/8	.063
-4	1/4"	17/64	1-1/8	.063
-5	5/16"	21/64	1-3/8	.063
-6	3/8"	25/64	1-5/8	.063
-7	7/16"	29/64	1-13/16	.109
-8	1/2"	33/64	2	.109


## SPECIAL FABRIC ATTACH LARGE AREA WASHERS

### 2024-T3 ALUMINUM

Sold only in boxes of 100. (For use with sheet metal screw TSA-; see index.)

PART NUMBER	HOLE DIA.	O.D.	THICKNESS
1/8 - 1/2	1/8"	1/2"	.016
1/8 - 3/4	1/8"	3/4"	.016

## 100° COUNTER- SUNK FAIRING WASHERS



For use with 100° flat-head screws to provide reinforced, low-profile attachments. Made of spring steel. Sold only in packages of 100.

PART NUMBER	SCREW SIZE	A	B	T
A3236-012-24A	#6	.500	.140-.147	.012
A3135-017-24A	#8	.562	.171	.017
A3235-020-24A	#10	.750	.196	.020
A3475-028-24A	428	.812	.255-.260	.028

## 100° COUNTERSUNK FINISHING WASHERS

Dash Number is Screw Size:

**RAISED: 601-4**

**FLUSH: 603-6**


**Nickel Plated Brass**

Sold only in packages of 100.



## LOCK WASHERS AN935 MS35338

Carbon Steel per Spec. QQ-S-633, Cadmium Plated per QQ-P-416, Type II, Class C.



AN DASH NUMBER	MS DASH NUMBER	SCREW OR BOLT SIZE	OUTSIDE DIA. (Inches)	THICKNESS (Inches)	PKG. QTY.
-4	-40	#4	.212	.025	100
-6	-41	#6	.253	.031	100
-8	-42	#8	.296	.040	100
-10	-43	#10	.337	.047	100
-416	-44	1/4"	.493	.062	100
-516	-45	5/16"	.591	.078	100
-616	-46	3/8"	.688	.094	50
-716	-47	7/16"	.784	.109	50
-816	-48	1/2"	.879	.125	50

## SHAKEPROOF WASHERS; INTERNAL & EXTERNAL TEETH

1050 Spring Steel, Cadmium Plated, Dichromate Dip. Sold only in packages of 100.

### A Type; Internal Teeth



**MS 35333  
AN 936**

MS35333 DASH NO.	AN936 DASH NO.	SCREW OR BOLT SIZE
-36	-A4	#4
-37	-A6	#6
-38	-A8	#8
-39	-A10	#10
-40	-A416	1/4"
-41	-A516	5/16"
-42	-A616	3/8"
-43	-A716	7/16"
-44	-A816	1/2"

### B Type; External Teeth



**MS 35335  
AN 936**

MS35335 DASH NO.	AN936 DASH NO.
-29	-B4
-30	-B6
-31	-B8
-32	-B10
-33	-B416
-34	-B516
-35	-B616
-36	-B716
-37	-B816