





NUTS

Produced in accordance with MIL-N-6034. Steel nuts are cadmium plated and dichromate dipped per Specification QQ-P-416, type II, Class 3.

				Dash No.	Diameter and Thread	Wrench Size	Pkg. Qty.
AN 310 Castellated	AN 315 Plain	AN 316 Check	AN 320 Shear	-3	10-32	3/8	50 *
				-4	1/4-28	7/16	50 *
				-5	5/16-24	1/2	50 *
				-6	3/8-24	9/16	25 *
				-7	7/16-20	5/8	25 *
				-8	1/2-20	3/4	25 *

	Order By This Number	Other Part Nos. as indicated in description	Thread	Wrench Size	Pkg. Qty.
 <p>STEEL MACHINE SCREW NUTS AN340 Coarse Thread AN345 Fine Thread Passivated Corrosion-resistant, Cadmium Plated per QQ-P-416. Spec. MIL-S-933</p>	-4		4-40	1/4	100
	-6		6-32	5/16	100
	-8		8-32	11/32	100
	-10		10-32	3/8	100
 <p>WING NUTS AN350 Commercial steel, cadmium plated per Specification QQ-P-416. Lockwire hole in one wing.</p>	-632		6-32		*
	-832		8-32		*
	-1032		10-32		*
	-4		1/4-28		*
	-5		5/16-24		*
	-6		3/8-24		*
 <p>PALNUTS AC356 (MS27151) Stamped Carbon Steel, Cadmium Plated per Spec. QQ-P-416.</p>	AC356-832	-6	8-32	11/32	100
	AC356-1032	-7	10-32	3/8	100
	AC356-428	-13	1/4-28	7/16	100
	AC356-524	-16	5/16-24	1/2	100
	AC356-624	-19	3/8-24	9/16	100
	AC356-720	-21	7/16-20	5/8	100
	AC356-820	-24	1/2-20	3/4	100
 <p>CONTINENTAL EXHAUST NUTS BRASS Meets NAF-213790 (3AC6203-) STEEL LOCKNUT (USAF46A1135-) BRASS LOCKNUT</p>	Continental Part Nos.				
	21247	-4	1/4-28	7/16	*
	22022	-5	5/16-24	1/2	*
	536038	-428	1/4-28	7/16	*
	642803		1/4-28	7/16	*
 <p>STEEL EXHAUST NUT MS35690 For LYCOMING Plated carbon steel, manufactured to procurement specification FF-N-836.</p>	Lycoming Part No.				
	STD 1410	-502	5/16-18	1/2	*



LIGHT WEIGHT, SELF-LOCKING, 450° F NUTS

Steel, heat treated, cadmium plated, dry film lubricated. For use in applications up to 450° F. Meets salt spray requirements.

Particularly suited for use in blind close clearance areas. The counterbore provided eliminates necessity for shimming to prevent bottoming on the imperfect thread.

For countersunk rivet holes add K to NAS Part Number or BC to Mfr's Part Number. For example: NAS680A-06K or RM52LHTA51-62BC. Prices on application. Larger sizes also POA.

Order from this page by NAS Number.

	NAS NUMBER	MS NUMBER	MANUFACTURER'S PART NUMBER	THREAD SIZE	WRENCH SIZE	PKG. QTY.
	NAS679A	MS21040-L06	RMLHTM-62W	6-32	5/16"	100
		MS21040-L08	RMLHTM-82W	8-32	11/32"	100
		MS21040-L3	RMLHTM-02W	10-32	3/8"	100
		MS21040-L4	RMLHTE-048W	1/4-28	7/16"	50
		MS21040-L5	RMLHTE-054W	5/16-24	1/2"	50
		MS21040-L6	RMLHTE-064	3/8-24	9/16"	50
	NAS1291	MS21042-L06	RM52LH3324-62	6-32	3/16"	100
		MS21042-L08	RM52LH3324-82	8-32	7/32"	100
		MS21042-L3	RM52LH3324-02	10-32	1/4"	100
		MS21042-L4	RM52LH3324-048	1/4-28	5/16"	100
		MS21042-L5	RM52LH3324-054	5/16-24	3/8"	50
		MS21042-L6	RM52LH3324-064	3/8-24	7/16"	50

	NAS NUMBER	MANUFACTURER'S PART NUMBER	THREAD SIZE	RIVET HOLE SPACING	RIVET HOLE SIZE	PACKAGE QTY.
	NAS680A	RM52LHTA51-62	6-32	.68	.098	50
		RM52LHTA51A-82	8-32	.68	.098	50
		RM52LHTA51A-02	10-32	.68	.098	50
		RM52LHTA51-048	1/4-28	1.00	.098	25
		RM52LHTA51-054	5/16-24	1.00	.130	25
		RM52LHTA51-064	3/8-24	1.00	.130	25
	NAS682A	RM52LHTA57-62	6-32	.312	.098	50
		RM52LHTA57-82	8-32	.312	.098	50
		RM52LHTA57-02	10-32	.312	.098	50
		RM52LHTA57-048	1/4-28	.312	.098	25
		RM52LHTA57-054	5/16-24	.312	.130	25
	NAS686A	RM52LHTA521-62	6-32	.68	.098	50
		RM52LHTA521-82	8-32	.68	.098	50
		RM52LHTA521-02	10-32	.68	.098	50
		RM52LHTA521-048	1/4-28	1.00	.098	25
		RM52LHTA521-054	5/16-24	1.00	.130	25
		RM52LHTA521-064	3/8-24	1.00	.130	25
	NAS697A	RM52LHTA51M-62	6-32	.343	.066	50
		RM52LHTA51M-82	8-32	.468	.098	50
		RM52LHTA51M-02	10-32	.500	.098	50
		RM52LHTA51M-048	1/4-28	.562	.098	25
		RM52LHTA51M-054	5/16-24	.718	.130	25
	NAS698A	RM52LHTA55M-62	6-32	.243	.066	50
		RM52LHTA55M-82	8-32	.331	.098	50
		RM52LHTA55M-02	10-32	.354	.098	50
		RM52LHTA55M-048	1/4-28	.398	.098	25
		RM52LHTA55M-054	5/16-24	.508	.130	25
	NAS1068A	RM52LHTA521M-62	6-32	.343	.066	50
		RM52LHTA521M-82	8-32	.468	.098	50
		RM52LHTA521M-02	10-32	.500	.098	50
		RM52LHTA521M-048	1/4-28	.562	.098	25

