

LPS[®] NoFLASH[®]

ELECTRO CONTACT CLEANER



Specifications:

- Boeing D6-17487 Rev. P
- McDonnell Douglas CSD #1

APPLICATIONS

- Contacts
- Controls
- Circuit breakers
- Generators
- Instrumentation
- Meters
- Printed circuit boards
- Relays
- Sensors
- Signals
- Switches
- Telecommunication equipment
- Terminals



PROPERTIES

Flash Point:

None

Specific Gravity:

1.304 @ 77°F (25°C)

KB Value:

80

% Non-Volatiles:

100 ppm. max.

Dielectric Strength and Breakdown Voltage (ASTM D-877):

9,000 Volts

Propellant:

HFC - 134a

VOC:

70.1%, 913 g/L, 7.6 lbs./gal. Per CARB / OTC Regulations

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

PACKAGE

Net Contents

12 wt. oz. /340 g./268 ml. aerosol

NOT AVAILABLE IN CANADA

Part No.

04016

FEATURES

- Non-flammable precision cleaning
- Unique alternative to HCFC cleaners
- Does not contain chlorinated solvents
- Non-conductive
- Fast evaporation
- Quick penetration
- No residue
- Safe to use on most surfaces, test for compatibility on ABS, acrylics, polystyrene and polycarbonate
- Inverta Spray Valve lets you spray in an upright or inverted position
- VOC compliant in California



Nonfood Compounds Program Listed
Category Code: K2 Registration # 131303

LPS Laboratories • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2012 LPS Laboratories • LPS[®] and NoFlash[®] are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2075 • Rev. 5/2012